

**NEW!**

# THE STICKS

**testo**

## Powerful, Pocket-Size Meters



- 405-V2 Air Velocity Meter
- 505-P2 Digital Manometer
- 605-H1/605-H2 Digital Psychrometers
- 905-T1 Type K Thermometer (Penetration)
- 905-T2 Type K Thermometer (Surface)
- 825 IR Thermometer Series

### STICKS Features:

- Simple push-button operation
- Fits in your pocket
- Rugged and reliable
- Fast and accurate high-tech sensors
- Low cost
- Pivoting head on most models for easy viewing



**Call Testo today: 800-227-0729**

**[www.testo.com](http://www.testo.com)**

Testo, Inc. 35 Ironia Rd., Flanders, NJ 07836 Tel. (973) 252-1720 Fax (973) 252-1729

Work **SMARTER**...Not Harder

**testo**



## testo 405-V2 Air Velocity Meter

The testo 405-V2 is the first low cost mini-anemometer to measure temperature, velocity and volume flow. Design features allow for fast and easy measurement.

### Features:

- Micro, precision hot-wire sensor fits into small openings
- Measures temperature, velocity and volume flow
- Probe universal joint bends to fit in your pocket
- Auto-off function
- Rotating cap protects sensor during storage
- Pocket clip

### Specifications

<b>Range:</b>	0 to 2000 fpm (10m/s) 0 to 99,990 CFM (99,990m <sup>3</sup> /hr)
<b>Resolution:</b>	0.1fpm (0.01m/s) 0.1°F/°C
<b>Accuracy:</b>	± 5% of m.v.
<b>Operating temp.:</b>	-5°F to 122°F (-20°C to 50°C)
<b>Storage temp.:</b>	-5°F to 140°F (-20°C to 70°C)
<b>Battery:</b>	3 x AAA cells
<b>Battery life:</b>	Approx. 20h
<b>Probe stem:</b>	0.63" dia. (.47" dia. @ sensor) 8" (folded); 13" (extended)
<b>Warranty:</b>	1 year

## testo 905-T1 Type K Thermometer (penetration) testo 905-T2 Type K Thermometer (surface)

The testo 905-T1 is one of the fastest and most accurate mini-thermometers in the world. Above 480°F the 905-T1 has an accuracy of <math>\pm 4.5^\circ\text{F}</math>. The testo 905-T2 Surface Thermometer is spring-loaded to guarantee fast and accurate measurements on both smooth or uneven surfaces.

### Features:

- Industrial Type K Sensor
- Fast measurements
- High range (900°F short-term)
- C°/F° selectable
- Pocket clip

### Specifications

<b>Range:</b>	-60°F to 660°F (-50°C to 350°C) (short term) 900°F
<b>Resolution:</b>	0.1°/1.0°
<b>Accuracy:</b>	± 1°F (to 200°F) ± 1% m.v. (+200°F)
<b>Response:</b>	<10 sec. (T1), < 4 sec. (T2)
<b>Battery:</b>	3V (CR2032)
<b>Battery life:</b>	Approx. 100h
<b>Probe stem:</b>	0.12" dia. (T1), 0.40" dia. (T2) 7.9" length (T1), 5.9" length (T2)
<b>Warranty:</b>	1 year

## testo 505-P2 Manometer

The testo 505-P2 Digital Manometer is compact and very easy to operate. The magnetic back attaches to ducts, furnaces, etc. for hands-free use.

### Features:

- One button easy operation
- Not position sensitive
- Compact size fits in pocket or tool box
- Auto-off function
- Displays " H<sub>2</sub>O, PSI, or hPa
- Magnetic back

### Specifications

<b>Range:</b>	-10" to 52" H <sub>2</sub> O; 1.88 PSI; 130hPa
<b>Resolution:</b>	0.01" H <sub>2</sub> O
<b>Accuracy:</b>	0.25" H <sub>2</sub> O
<b>Operating temp.:</b>	32°F to 105°F
<b>Storage temp.:</b>	-5°F to 140°F
<b>Battery:</b>	2 x (CR2032)
<b>Battery life:</b>	Approx. 100h
<b>Pressure ports:</b>	1/8" tapered
<b>Warranty:</b>	1 year

## testo 825 Non-Contact/Contact Thermometers

The testo 825 series is two thermometers in one rugged, compact instrument. It combines the fast-acting infrared side for measuring difficult-to-access areas with a convenient contact side for measuring unknown or low emissivity materials. Gives fast and accurate measurements in seconds.

### Features:

- Quick and safe non-contact measurements
- User-selectable ascending or descending visual alarm
- Adjustable emissivity (0.20 to 1.00)
- Includes belt clip/wall holder and TopSafe to protect from impact, dust and water
- Both 825-T2 & 825-T4 offer precise laser sighting and audible alarms

### Specifications

<b>Range:</b>	-60°F to 750°F
<b>Resolution:</b>	0.9°F
<b>Accuracy:</b>	± 3.5°F or ± 2% of reading
<b>Ratio:</b>	6:1 measuring spot
<b>Response:</b>	<2 sec.
<b>Operating temp.:</b>	32°F to 122°F
<b>Battery:</b>	2 x lithium 2032 (825-T1 & T3) 2 x AAA round cell (825-T2 & T4)
<b>Battery life:</b>	Approx. 10h (825-T1 & T3) Approx. 20h (825-T2 & T4)
<b>Warranty:</b>	1 year

## testo 605-H1 & H2 Digital Psychrometers

The testo 605 Series Humidity STICKS provide fast and accurate %RH, temperature and dew point readings.

### Features:

- Accurate & long-term stability
- One button, user-friendly operation
- Handy pocket clip
- Sensor not affected by water
- Rotating cap protects sensor during storage
- Includes pocket clip and duct holder

### Specifications

<b>Dewpoint (H1 only):</b>	-58°F to 212°F
<b>Range:</b>	5 to 95%RH 32°F to 122°F
<b>Wet bulb (H-2 only):</b>	-4°F to 160°F
<b>Resolution:</b>	0.1%RH 0.1°F
<b>Accuracy:</b>	1°F ± .5°F
<b>Operating temp.:</b>	-5°F to 122°F
<b>Battery:</b>	CR2032
<b>Battery life:</b>	Approx. 200h
<b>Probe stem:</b>	0.47" dia. 4.9" length
<b>Storage:</b>	-4°F to 160°F
<b>Warranty:</b>	1 year

## ORDERING INFORMATION

Description	Part #
testo 405-V2	0560.4052
testo 505-P2	0560.5052
testo 605-H1 (dewpoint)	0560.6051
testo 605-H2 (wet bulb)	0560.6052
testo 825-T1	0560.8255
testo 825-T2 (with laser)	0560.8256
testo 825-T3 (with surface probe)	0560.8257
testo 825-T4 (with surface probe and laser)	0560.8258
testo 905-T1	0560.9051
testo 905-T2	0560.9052
Wall Bracket (5pcs.)	0554.1783

**Your local distributor is:**



Work **SMARTER**...Not Harder